

VANDALPROOF METAL CABINET LOUDSPEAKER

› SENTRY4/STC



ARCHITECTS & ENGINEERS SPECIFICATION

This unit shall be the PENTON model SENTRY4/STC or equal and approved. The loudspeaker cabinet shall be a two-part epoxy coated steel fabrication with an inner metal mesh grille covering the drive unit. The speaker assembly shall comprise of an 80mm diameter dual coned mid-range loudspeaker and shall be fitted with a 4 watt/100 volt line factory fitted transformer with the power taps clearly marked on the assembly.

Cable entry will be via 2 x 20mm cable entries located at the top of the cabinet and via concealed universal mounting holes (for standard UK electrical junction boxes) at the rear.

The loudspeaker shall have a wide-angle dispersion. The cone shall be a damped, high compliance type with a smooth extended frequency response.

The SENTRY4/STC will be suitable for voice alarm applications and will be supplied with ceramic terminals to take 2 x 2.5mm² conductors and a thermal fuse rated at 150°.

This loudspeaker must be complaint to BS5839 part 8 & EN60849.

RATED POWER	4w
TAPPINGS 100v LINE	4/2/1/0.5w
EFFECTIVE FREQUENCY RANGE	170 - 20kHz
SPL @ 1w/m (TEST SIGNAL 100Hz - 10kHz)	87dB
DISPERSION AT 1k/2kHz	180/120
AXIAL Q FACTOR AT 1k/2kHz	3.2/3.8
COLOUR	WHITE RAL9016

All units to be tested in accordance with BSEN60268-5



Penton UK Ltd

Unit 2 Teville Industrials | Dominion Way | Worthing | West Sussex | BN14 8NW

T: +44 (0)1903 215315 | F: +44(0)1903 215415 | E: SALES@PENTONUK.CO.UK

www.pentonuk.co.uk

ISSUE NOVEMBER 2011